#3

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of: Uzi Gati

Application No.: 09/873,331 | Group Art Unit: 3722

Filed: June 5, 2001 | Examiner: To Be Assigned

For: CUTTING TOOL ASSEMBLY | Attorney Docket No.: 10236-027

CLAIM TO PRIORITY
TRANSMITTAL OF CERTIFIED COPY OF PRIORITY DOCUMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Enclosed is a certified copy of Israeli Patent Application Number 136564 filed June 5, 2000, in Israel, from which priority has been claimed in this application.

Respectfully submitted,

Date August 15, 2001

Nanda K. Alapati Reg. No. 39,893
For: Marcia H. Sundeen Reg. No. 30,893
PENNIE & EDMONDS LLP
1667 K Street, N.W.
Washington, DC 20006
(202) 496-4400

Enclosure

מדינת ישראל
STATE OF ISRAEL

Ministry of Justice
Patent Office

משרד המשפטים
לשכת הפטנטים

זאת לתעודה כי רצופים בזה העתקים נכונים של המסמכים שהופקדו לכתחילה עם הבקשה לפטנט לפי הפרטים הרשומים בעמוד הראשון של הנספח.

This is to certify that annexed hereto is a true copy of the documents as originally deposited with the patent application of which particulars are specified on the first page of the annex.

This 24-05-2001 היום

24-05-2001

רשם הפטנטים
Commissioner of Patents

נתאשר
Certified

חוק הפטנטים, תשכ"ז - 1967
PATENTS LAW, 5727-1967

בקשה לפטנט
Application for Patent

לשימוש הלשכה
For Office Use

מספר: Number	136564
תאריך: Date	05 -06- 2000
הוקדם / נדחה Ante / Post-dated	

אני, (שם המבקש, מענו - ולגבי גוף מאוגד - מקום התאגדותו)
I, (Name and address of applicant, and, in case of a body corporate, place of incorporation)

ישקר בע"מ, חברה ישראלית, ת.ד. 11, תפן 24959, ישראל
Iscar Ltd., Israeli Company, P.O.Box 11, Tefen 24959, Israel

הממציא: עוזי גתי
The inventor: Uzi Gati

בעל אמצאה מכח הדין
Owner, by virtue of Right of Law of an invention, the title of which is:

(בעברית)
(Hebrew)
כלי חיתוך

(באנגלית)
(English)
Cutting Tool Assembly

מבקש בזאת כי ינתן לי עליה פטנט.
hereby apply for a patent to be granted to me in respect thereof.

* בקשת חלוקה Application for Division	* בקשת פטנט מוסף - Application for Patent of Addition	* דרישת דין קדימה Priority Claim		
מבקשת פטנט from Application	* לבקשה/לפטנט to Patent/Application	מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country
מס' No. _____ מיום dated _____	מס' No. _____ מיום dated _____			
* יפוי כח: כללי/~~מיוחד~~ - ~~רצוף בזה/עוד יוגש~~ P.O.A.: general/~~specific~~ - ~~attached/to be filed later~~ הוגש בענין Has been filed in case P 131260				
המען למסירת הודעות ומסמכים בישראל Address for Service in Israel				
Iscar Ltd. ישקר בע"מ Patent Department מחלקת פטנטים P.O.Box 11 ת. ד. 11 Tefen 24959 תפן 24959				
חתימת המבקש Signature of Applicant M. Kaye (Ref. No. 283-648230)		היום 5 בחודש June שנת 2000.		
				לשימוש הלשכה For Office Use

טופס זה, כשהוא מוטבע בחותם לשכת הפטנטים ומושלם במספר ובתאריך ההגשה, הינו אישור להגשת הבקשה שפרטיה רשומים לעיל.
This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application, the particulars of which are set out above.

* מחק את המיותר Delete whatever is inapplicable

כלי חיתוך

Cutting Tool Assembly

Iscar Ltd.

ישקר בע"מ

The inventor:

Uzi Gati

הממציא:

עוזי גתי

CUTTING TOOL ASSEMBLY

FIELD OF THE INVENTION

The present invention relates to a cutting tool assembly having an indexable cutting insert and more particularly to a cutting tool assembly for grooving operations in which the cutting insert is mechanically clamped.

BACKGROUND OF THE INVENTION

In such cutting tool assemblies the cutting insert is retained in an insert pocket defined between clamping surfaces of upper and lower jaws of the insert holder, generally referred to as clamping and base jaws, respectively. The insert holder can be a one-piece tool, or, the clamping jaw can be a separate member. In both cases, at least one screw is used for forcing the two jaws towards each other for secure retention of the cutting insert.

In order to uniquely determine the axial location of the cutting insert an axial stop is provided in the insert pocket. In some prior art cutting tool assemblies the stop is located on one of the clamping surfaces of the upper and lower clamping jaws. In such cases, the cutting insert has to be designed with an appropriate protrusion or recess, on the corresponding insert clamping abutment surface, for engaging the stop. In other prior art cutting tool assemblies, the stop is located at the rear of the insert pocket and the axial location of the cutting insert is fixed when

a section of the rear surface of the cutting insert abuts the stop. This arrangement has two disadvantages. First, it restricts the shape of the rear surface of the cutting insert. For double-ended grooving cutting inserts the rear surface is the non-operative front relief surface. Hence, this arrangement restricts the shape of the front relief surface of the cutting insert. Second, if the end portion of the cutting insert, associated with the operative cutting edge, were to break during a cutting operation, the section of the relief surface which would abut the stop on indexing the cutting insert, may well become damaged, in which case the cutting insert could not be indexed, preventing use of the cutting edge associated with the non-damaged end portion of the cutting insert.

To stabilize the cutting insert in the direction perpendicular to the axial direction, the clamping abutment surfaces of the cutting insert are formed with V-shaped protrusions (or grooves) and the clamping surfaces of the insert holder's jaws are formed with matching V-shaped grooves (or protrusions). According to some embodiments of such cutting tool assemblies, the cutting inserts have a stop-engaging protrusion (or recess) on one of their clamping abutment surfaces and the insert holders having a corresponding stop-engaging recess (or protrusion) on one of the clamping surfaces of one of their clamping jaws. The presence of such stop-engaging protrusions (or recesses) can be disadvantageous.

It is an object of the present invention to provide a double-ended grooving cutting insert that substantially overcomes the above mentioned disadvantages.

It is also an object of the present invention to provide an insert holder for retaining the above-mentioned grooving cutting insert.

SUMMARY OF THE INVENTION

In accordance with the present invention there is provided a cutting insert (24) comprising a central body portion (46) extending between two opposite end portions (48, 50), each end portion (48, 50) being provided with a cutting

edge (52); the central body portion (46) being provided with upper and lower clamping abutment surfaces (54, 56) with first and second side surfaces (58, 60) extending therebetween; at least one of the first and second side surfaces (58, 60) being provided with an axial location member (62, 70).

In accordance with one embodiment, the axial location member is a protrusion (62).

Generally, the protrusion (62) is square shaped.

In accordance with another embodiment of the present invention, the axial location member is a recess (70).

Preferably, the upper and lower clamping abutment surfaces (54, 56) are sloped, defining therebetween a variable distance, so that when the cutting insert (24) is viewed in an end view the distance between the upper and lower clamping abutment surfaces (54, 56) is a maximum at the first side surface (58) and a minimum at the second side surface (60).

If desired, the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped protrusions.

Further if desired, the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped grooves.

There is also provided in accordance with the present invention a cutting tool assembly (20) comprising:

a cutting insert holder (22); and

a cutting insert (24);

the cutting insert holder (22) comprising:

an upper clamping jaw (26) having an upper clamping surface (28);

a lower base jaw (30) having a lower clamping surface (32);

at least one clamping screw (34) passing through the upper clamping jaw (26) and threadingly connected to the lower base jaw (30);

an insert holder inner side surface (40) extending between the upper and lower clamping surfaces (28, 32);

an insert pocket (42) bound on two opposite sides by the upper and lower clamping surfaces (28, 32) and bound on a third side extending between the two opposite sides by the insert holder inner side surface (40); the insert holder inner side surface (40) being provided with a positioning member (45);

the cutting insert (24) comprising:

a central body portion (46) extending between two opposite end portions (48, 50), each end portion being provided with a cutting edge (52); the central body portion (46) being provided with upper and lower clamping abutment surfaces (54, 56) with first and second side surfaces (58, 60) extending therebetween; at least one of the first and second side surfaces (58, 60) being provided with an axial location member (62);

wherein the upper clamping abutment surface (54) abuts the upper clamping surface (28), the lower clamping abutment surface (56) abuts the lower clamping surface (32) and the positioning member (45) engages the axial location member (62) whereby the axial location of the cutting insert (24) is fixed.

In accordance with one embodiment, the axial location member is a protrusion (62) and the positioning member (45) is a rear surface of a recess (44) in the insert holder inner side surface (40).

Generally, the protrusion (62) is square shaped and the recess has a generally matching square shaped cross section.

In accordance with another embodiment, the axial location member is a recess (70) and the positioning member (45) is a protrusion on the insert holder inner side surface (40).

Preferably, the upper and lower clamping abutment surfaces (54, 56) are sloped, defining therebetween a variable distance, so that when the cutting insert (24) is viewed in an end view the distance between the upper and lower clamping abutment surfaces (54, 56) is a maximum at the first side surface (58) and a minimum at the second side surface (60) and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30),

respectively, are matchingly sloped.

If desired, the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped protrusions and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30), respectively, have the form of matching V-shaped grooves.

Further if desired, the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped grooves and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30), respectively, have the form of matching V-shaped protrusions.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a right perspective view of a cutting tool assembly in accordance with one preferred embodiment of the present invention with the cutting insert removed from the insert holder;

Fig. 2 is a left perspective view of the cutting tool assembly shown in Fig. 1;

Fig. 3a is a side view of the cutting insert shown in Figs. 1 and 2;

Fig. 3b is a top view of the cutting insert shown in Figs. 1 and 2;

Fig. 3c is a front view of the cutting insert shown in Figs. 1 and 2;

Fig. 4a is a partial side view of the insert holder shown in Figs. 1 and 2;

Fig. 4b is a cross-sectional view along line IVb-IVb in Fig. 4a;

Fig. 4c is a partial front view of the insert holder shown in Figs. 1 and 2;

Fig. 5 is a right perspective view of a cutting tool assembly in accordance with another preferred embodiment of the present invention with the cutting insert removed from the insert holder;

Fig. 6a is left perspective view of the cutting insert shown in Fig. 5;

Fig. 6b is a side view of the cutting insert shown in Figs. 5 and 6a;

Fig. 7 is a side view of a cutting tool assembly in accordance with the present

invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are sloped and the clamping surfaces of the insert holder's jaws are formed with matching slopes;

Fig. 8 is a side view of a cutting tool assembly in accordance with the present invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are formed with V-shaped protrusions and the clamping surfaces of the insert holder's jaws are formed with matching V-shaped grooves;

Fig. 9 is a side view of a cutting tool assembly in accordance with the present invention with the cutting insert removed from the insert holder, the clamping abutment surfaces of the cutting insert are formed with V-shaped grooves and the clamping surfaces of the insert holder's jaws are formed with matching V-shaped or protrusions;

Fig. 10a is a front view of a cutting insert having a protrusion on each of the side surfaces of the central body portion;

Fig. 10b is a side view of the cutting insert shown in Fig. 10a;

Fig. 11a is a front view of a cutting insert having a recess in each of the side surfaces of the central body portion; and

Fig. 11b is a side view of the cutting insert shown in Fig. 11a.

DETAILED DESCRIPTION OF THE INVENTION

Attention is first drawn to Figs. 1 to 4c, showing a cutting tool assembly **20** in accordance with the present invention comprising a cutting insert holder **22** and a cutting insert **24**. The cutting insert holder **22** comprises an upper clamping jaw **26** having an upper clamping surface **28** and a lower base jaw **30** having a lower clamping surface **32**. Two clamping screws **34** are used to securely clamp the cutting insert **24** between the upper and lower clamping surfaces. Each clamping screw **34** passes through a through bore **36** in the upper clamping jaw **26** and is threadingly connected to the lower clamping jaw via a threaded bore **38** in

the lower base jaw **30**. Between the upper and lower clamping surfaces extends an insert holder inner side surface **40**. An insert pocket **42**, for receiving and retaining the cutting insert **24**, is bound on two opposite sides by the upper and lower clamping surfaces and on a third side, extending between the two opposite sides, by the insert holder inner side surface **40**. The insert holder inner side surface is provided with a recess **44** having a rear surface **45** forming a positioning member for the determination of the axial location of the cutting insert.

The cutting insert **24** comprises a central body portion **46** extending between two opposite end portions **48**, **50**, the end portions being provided with cutting edges **52**. The central body portion **46** has upper and lower clamping abutment surfaces **54**, **56** with first and second side surfaces **58**, **60**, extending therebetween. The first side surface **58** is provided with a protrusion **62** forming an axial location member for the cutting insert. The protrusion **62**, in the embodiment shown, is square shaped and the recess **44** has a matching square shaped cross section for receiving the protrusion **62**.

When the cutting tool assembly is assembled, the upper clamping abutment surface **54** of the cutting insert **24** abuts the upper clamping surface **28** of the upper clamping jaw **26**, the lower clamping abutment surface **56** of the cutting insert abuts the lower clamping surface **32** of the base jaw **30** and the protrusion **62** engages the rear surface **45** of the recess **44**, whereby the axial location of the cutting insert **24** is fixed.

It should be noted that the cutting insert **24** has 180° rotational symmetry about an axis perpendicular to a longitudinal plane **P** of the cutting insert and passing through the center of the protrusion **62**. Hence, for a given orientation of the cutting insert, as best seen in Fig. 3a, one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the lower clamping abutment surface **56**. Clearly, as best seen in Figs. 1 and 2, the upper cutting edge is the operative cutting edge. It should further be noted that

since the present invention is directed to the axial location of the cutting insert and not to its specific shape or function, the cutting edges and the associated rake and relief surfaces are only shown schematically and it will be apparent that any required form of rake and relief surface and associated cutting edge can be used.

Attention is now drawn to Figs. 5 to 6b showing a cutting insert holder **64** and an associated cutting insert **66** in accordance with another embodiment of the present invention. In this embodiment the axial location of the cutting insert **66** is determined by the engagement of a protrusion **68** on the insert holder inner side surface **40** by a recess **70** in the first side surface **58** of the central body portion **46** of the cutting insert. As shown in Figs. 5 to 6b, there are two recesses **70** on the first side surface **58** of the central body portion **46**. Therefore, as with the above described first embodiment, the cutting insert has 180° rotational symmetry about an axis passing through the geometrical center of the side surfaces **58**, **60** of the central body portion **46** and perpendicular to a longitudinal plane of the cutting insert **66**. Hence, for a given orientation of the cutting insert, as best seen in Fig. 6b (which is similar to Fig. 3a), one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the lower clamping abutment surface **56**.

In the embodiments shown in Figs. 1 to 6b, the geometry of the upper and lower clamping abutment surfaces **54**, **56** is not detailed and these surfaces are shown schematically to be flat and parallel. Figs. 7 to 9 show different possible geometries for the upper and lower clamping abutment surfaces. Although these geometries are exemplified for the embodiment of the invention shown in Figs. 1 to 4c, they apply equally well to the embodiment of the invention shown in Figs. 5 to 6b. Preferably, as shown in Fig. 7, the upper and lower clamping abutment surfaces **54**, **56** are sloped so that when the cutting insert is viewed in an end view the distance between them is a maximum at the first side surface **58** and a minimum at the second side surface **60**. The upper and

lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have matching slopes. Hence, when the cutting insert **24** is clamped in the insert pocket **42** of the cutting insert holder **22**, the upper clamping abutment surface **54** of the cutting insert abuts the upper clamping surface **28** of the upper clamping jaw **26**, the lower clamping abutment surface **56** of the cutting insert abuts the lower clamping surface **32** of the lower base jaw **30**, the protrusion **62** on the first side **58** of the central body portion **46** of the cutting insert abuts the rear surface **45** of the recess **44** and the first side surface **58** abuts the insert holder side surface **40**.

If desired, as shown in Fig. 8, the upper and lower clamping abutment surfaces **54**, **56** have the form of V-shaped protrusions and the upper and lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have the form of matching V-shaped grooves.

Further if desired, as shown in Fig. 9, the upper and lower clamping abutment surfaces **54**, **56** have the form of V-shaped grooves and the upper and lower clamping surfaces **28**, **32** of the upper clamping jaw **26** and the lower base jaw **30**, respectively, have the form of matching V-shaped protrusions.

The cutting inserts **24**, **66** described above have axial location members only on one side surface **58** of the central body portion **46**. As a result, for a given orientation of the cutting insert, one of the cutting edges **52** is an upper cutting edge, associated with the upper clamping abutment surface **54**, whilst the other cutting edge **52** is a lower cutting edge, associated with the lower clamping abutment surface **56**. Attention is now drawn to Figs. 10a to 11b. Figs. 10a and 10b show a cutting insert **72** having two protrusions **62** both constituting axial location members. One protrusion **62** is on the first side surface **58** and the other protrusion **62** is on the second side surface **60**. As seen in Fig. 10b, both cutting edges **52** are upper cutting edges, associated with the upper clamping abutment surface **54**. Similarly, Figs. 11a and 11b show a cutting insert **74** having two axial location members **70'**, **70''**, both recesses. One recess **70'** is on

the first side surface **58** and the other recess **70''** is on the second side surface **60**. The dashed lines represent a hidden recess. As seen in Fig. 11b, both cutting edges **52** are upper cutting edges associated with the upper clamping abutment surface **54**.

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications can be made without departing from the spirit or scope of the invention as hereinafter claimed. For example, the shape of the axial location member of the cutting insert and the positioning member of the cutting insert holder do not necessarily have to be square shaped, they can be round, elliptical or any other convenient shape.

CLAIMS:

1. A cutting insert (24) comprising a central body portion (46) extending between two opposite end portions (48, 50), each end portion (48, 50) being provided with a cutting edge (52); the central body portion (46) being provided with upper and lower clamping abutment surfaces (54, 56) with first and second side surfaces (58, 60) extending therebetween; at least one of the first and second side surfaces (58, 60) being provided with an axial location member (62, 70).

2. A cutting insert in accordance with Claim 1, wherein the axial location member is a protrusion (62).

3. A cutting insert in accordance with Claim 2, wherein the protrusion (62) is square shaped.

4. A cutting insert in accordance with Claim 2, wherein the axial location member is a recess (70).

5. A cutting insert in accordance with Claim 1, wherein the upper and lower clamping abutment surfaces (54, 56) are sloped, defining therebetween a variable distance, so that when the cutting insert (24) is viewed in an end view the distance between the upper and lower clamping abutment surfaces (54, 56) is a maximum at the first side surface (58) and a minimum at the second side surface (60).

6. A cutting insert in accordance with Claim 1, wherein the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped protrusions.

7. A cutting insert in accordance with Claim 1, wherein the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped grooves.

8. A cutting tool assembly (20) comprising:

a cutting insert holder (22); and

a cutting insert (24);

the cutting insert holder (22) comprising:

an upper clamping jaw (26) having an upper clamping surface (28);

a lower base jaw (30) having a lower clamping surface (32);

at least one clamping screw (34) passing through the upper clamping jaw (26) and threadingly connected to the lower base jaw (30);

an insert holder inner side surface (40) extending between the upper and lower clamping surfaces (28, 32);

an insert pocket (42) bound on two opposite sides by the upper and lower clamping surfaces (28, 32) and bound on a third side extending between the two opposite sides by the insert holder inner side surface (40); the insert holder inner side surface (40) being provided with a positioning member (45);

the cutting insert (24) comprising:

a central body portion (46) extending between two opposite end portions (48, 50), each end portion being provided with a cutting edge (52); the central body portion (46) being provided with upper and lower clamping abutment surfaces (54, 56) with first and second side surfaces (58, 60) extending therebetween; at least one of the first and second side surfaces (58, 60) being provided with an axial location member (62);

wherein the upper clamping abutment surface (54) abuts the upper clamping surface (28), the lower clamping abutment surface (56) abuts the lower clamping surface (32) and the positioning member (45) engages the axial location member (62) whereby the axial location of the cutting insert (24) is fixed.

9. A cutting tool assembly in accordance with Claim 8, wherein the axial location member is a protrusion (62) and the positioning member (45) is a rear surface of a recess (44) in the insert holder inner side surface (40).

10. A cutting tool assembly in accordance with Claim 9, wherein the protrusion (62) is square shaped and the recess has a generally matching square shaped cross section.

11. A cutting tool assembly in accordance with Claim 9, wherein the axial location member is a recess (70) and the positioning member (45) is a protrusion on the insert holder inner side surface (40).

12. A cutting tool assembly in accordance with Claim 8, wherein the upper and lower clamping abutment surfaces (54, 56) are sloped, defining

therebetween a variable distance, so that when the cutting insert (24) is viewed in an end view the distance between the upper and lower clamping abutment surfaces (54, 56) is a maximum at the first side surface (58) and a minimum at the second side surface (60) and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30), respectively, are matchingly sloped.

13. A cutting tool assembly in accordance with Claim 8, wherein the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped protrusions and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30), respectively, have the form of matching V-shaped grooves.

14. A cutting tool assembly in accordance with Claim 8, wherein the upper and lower clamping abutment surfaces (54, 56) have the form of V-shaped grooves and the upper and lower clamping surfaces (28, 32) of the upper clamping jaw (26) and the lower base jaw (30), respectively, have the form of matching V-shaped protrusions.

M. Kaye


34
22
20
34
28
26
40
44
46
32
24
45
30
52
42
50
60
48

Fig. 1


20
50
46
54
48
52
62
A
58
24
22

Fig. 2



Fig. 3a



Fig. 3b



Fig. 3c



Fig. 4a



Fig. 4b



Fig. 4c



Fig. 5



Fig. 6a



Fig. 6b



Fig. 7



Fig. 8



Fig. 9



Fig. 10a



Fig. 10b



Fig. 11a



Fig. 11b